

**Application
Parameters**



Indoor (room sensor)

Measuring value:

Output signal:

Measuring range:

Temperature/Humidity	DC 0...5 V DC 2...10 V DC 0...10 V MP-Bus	0...50°C/0...100% r.H.	22RTH-19-1	Active & NFC
----------------------	--	------------------------	-------------------	-----------------

Active & NFC: Measuring range freely adjustable with app

**Application
Parameters**



Duct

Point Measurement

Output Signal Active Humidity:

DC 0...5 V, DC 0...10 V	22DTH-11M
DC 0...5 V, DC 0...10 V	22DTH-11MM
4...20 mA	22DTH-13M
DC 0...5 V, DC 0...10 V	22DTH-15M
DC 0...5 V, DC 0...10 V	22DTH-16M

**Application
Parameters**



Outdoor

Output Signal Active Humidity:

DC 0...5 V, DC 0...10 V	22UTH-11	DC 0...5 V, DC 0...10 V	22UTH-150X
DC 0...5 V, DC 0...10 V	22UTH-110M	DC 0...5 V, DC 0...10 V	22UTH-160X
DC 0...5 V, DC 0...10 V	22UTH-110X		
4...20 mA	22UTH-13		
4...20 mA	22UTH-130X		